SOHAM INDUSTRIAL MACHINERY LTD.

Primary Requirement for

Dhoopbatti counting & packing machine

- Power Supply nearest to machine 2HP 1 phase. MCB-10Amp (3 core)-1.
- Air compressor 1.5HP with100 Galan tank/ 100litter- 1(10mm PU pipe connector and manual valve at Air delivery point)
- Req. air Connection 10 mm PU pipe nearest to machine
- BOPP roll as per your packing size (20 micron -plain) (Heat Sealable).
- Send us details for sticks/ pouch.
- Send us min. 5 kg. Dhoopbatti Skg Roll for machine testing.
- We provide only 2 Shute with machine.
- This machine is only for BOPP PLAIN ROLL
- For printed roll required eye mark system (charges will extra)
- You have to buy extra Shute for big pouch.
- Inform us your factory time and off day.
- Payable service available any time.
- Lifetime telephonic service free (9 AM to 6 PM, Sunday weekly off)
- You have to provide responsible person at the time of training and installation.
- Training & Installation at your site by our engineer (you have to bear to &FRO tickets, all the meals and lodging) (We are not available during corona time, we provide installation video and installation by video calling.)

Required Roll Width (max. weight of each rolls is 7 Kgs.)

Sr. No.	No. of Dhoopbatti	Width of BOPP Roll
1	5 to 10 Dhoopbatti	140 mm
2	11 to 15 Dhoopbatti	180 mm

Required rolls core id is 3 inches

Mr. Vishal sardhara +91 7567380501

Spare Department +91 9879027848

DHOOP STICK COUNTING AND PACKING MACHINE

